

Lubrication syringe

Lubrication syringes are available in many different possible combinations, depending on type of grease (or oil) and the size of the needle pre-defined. A selection of these are presented in the table below. For other types, please contact Rollco.

Lubrication grease:

- 00 For general applications
- 01 For low-friction, low-noise applications
- 02 For clean room applications
- 03 For clean room and vacuum environment applications
- 04 For high-speed applications
- 05 For micro-oscillation applications

Lubrication oil:

For general applications, ISO V32-68



General Data

Lubrication Syringe

LUB - 01 - 18G

Lubricant
 Lubrication grease:
 00 (For general applications)
 01 (For low-friction, low-noice applications)
 02 (For clean room applications)
 03 (For clean room and vacuum enviromen applicatioin)
 04 (For-high speed applications)
 05 (For micro-oscillation applications)
 Lubrication oil:
 11 (For general applications, ISO V32-68)

Needle model
 21G (5M/5W)
 19G (7M/7W)
 18G (9M/9W/12M/12W)
 15G (15M / 15W)

Designation	Compatible with	Lubricant	Needle model
LUB-00-21G	MR5/MR5W	00, for general applications	21G
LUB-00-19G	MR7/MR7W	00, for general applications	19G
LUB-00-18G	MR9/MR9W	00, for general applications	18G
LUB-04-18G	MR12/MR12W	04, for high-speed applications	18G
LUB-00-15G	MR15/MR15W	00, for general applications	15G