# WB



Dimensions in mm. Other tolerances according to standard shaft W.

Length tolerance: ± 3 mm, separating cut deburred.
Distance tolerance ± 0,2mm, P1 = P2
Positional tolerance of thread Ø (± 0,2 mm).

Thread depth = A
Thread dimension = C and S.


Other pitch available on request.

Contact us for CAD-files.

**Material:** Quenched and tempered steel Cf53 / 1.1213 / C53G
**Surface hardness:** 59 HRC min.
**Standard Tolerance:** ISO h6


Every care has been taken to ensure the accuracy of the information in this document, but we take no liability for any errors or omissions. We reserve the right to make changes without prior notice.

# Dimensions




| Designation | S | A | C | T | P1 | P | Lw (mm) | Diameter |
|---|---|---|---|---|---|---|---|---|
| **WB12** | 5 | 7 | 2 | M4 | 37.5 | 75 | 6000 | 12 |
| **WB16** | 6 | 9 | 2.5 | M5 | 50 | 100 | 6000 | 16 |
| **WB20** | 7 | 11 | 3 | M6 | 50 | 100 | 6000 | 20 |
| **WB25** | 9 | 15 | 3 | M8 | 60 | 120 | 6000 | 25 |
| **WB30** | 11 | 17 | 3.5 | M10 | 75 | 150 | 6000 | 30 |
| **WB40** | 11 | 19 | 4 | M10 | 100 | 200 | 6000 | 40 |


Every care has been taken to ensure the accuracy of the information in this document, but we take no liability for any errors or omissions. We reserve the right to make changes without prior notice.