

Mounted Rail and NSW/NSA/NSD/NSDA Slider

TLC43 - 1 - NSW - 3 - A - 2Z - 1000 - 20 - 20

Rail type

TL
UL
KL (only available for size 43 and 63)

Fixing holes

C (Counterbore)
V (Countersunk)

Rail size

18, 28, 43 or 63

No. of sliders on each rail

Slider type (see table below)

NSW/NSA
NSD/NSDA

Number of rollers

3, 4, 5 or 6

Configuration (depending on type of slider)

Roller seal

Steel cover disc 2Z (standard)
Rubber seal 2RS

Rail length (mm)

Distance from end of rail to center of first hole

Distance from center of last hole to rail end

Note: For heavy preload please contact Rollco

Rail composition: 1x3280+1x1280 (only for joint processed rails)

Hole pattern: 40-40x80-40//40-15x80-40 (please always specify the hole pattern separately)

Rail	Hole facing rail on slider	Hole parallel to rail on slider
TL. / UL.	NSW	NSD
KL.	NSA	NSDA

NSW/NSA/NSD/NSDA Slider

NSW43 - 4 - B - 2RS

Slider type (see table below)

NSW/NSA

NSD/NSDA

Slider size

18, 28, 43 or 63

Number of rollers

3, 4, 5 or 6

Configuration (depending on type of slider)

Roller seal

Steel cover disc 2Z (standard)

Rubber seal 2RS

Rail	Hole facing rail on slider	Hole parallel to rail on slider
TL. / UL.	NSW	NSD
KL.	NSA	NSDA

Mounted Rail and CSW/CSWK Slider

TLC43 - 2 - CSW43-150-2Z-A-T - 3000 - 20 - 20

Rail type

TL

UL

KL (only available for size 43 and 63)

Fixing holes

C (Counterbore)

V (Countersunk)

Rail size

18, 28, 43 or 63

No. of sliders on each rail**Slider type**

CSW/CSWK

Slider size

18, 28, 43 or 63

Slider body length**Roller seal**

Steel cover disc 2Z (standard)

Rubber seal 2RS

Configuration (depending on type of slider)**Type of wiper** (T or U)**Rail length (mm)****Distance from end of rail to center of first hole****Distance from center of last hole to rail end**

Note: For heavy preload please contact Rollco

Rail composition: 1x3280+1x1280 (only for joint processed rails)

CSW/CSWK Slider

CSW43 - 150 - 2Z - A - T

Slider type
CSW/CSWK

Slider size
18, 28, 43 or 63

Slider body length

Roller seal
Steel cover disc 2Z (standard)
Rubber seal 2RS

Configuration (depending on type of slider)

Type of wiper (T or U)

Rail

TLC43 - 0 - 1000 - 20 - 20

Rail type

TL
UL
KL (only available for size 43 and 63)

Fixing holes

C (Counterbore)
V (Countersunk)

Rail size

18, 28, 43 or 63

No. of sliders on each rail**Rail length (mm)****Distance from end of rail to center of first hole****Distance from center of last hole to rail end**

Note: For longer lengths, please contact Rollco

Rail composition: 1x880+2x2400 (only for joint processed rails)

Hole pattern: 40-10x80-40//40-29x80-40//40-29x80-40 (please always specify the hole pattern separately)

Wipers

ZK-WNS - 28

Wiper type

ZK-WNS for NSW/NSA/NSD/NSDA
ZK-WCST for CSW/CSWK with T-Rail
ZK-WCSU for CSW/CSWK with U-Rail
ZK-WCSK for CSW/CSWK with K-Rail

Size

18, 28, 43 or 63

Note on ordering: Every kit contains a pair of wipers. Two wipers per slider are always required.